

**OLEOSTATIC® mantlade klassiska kilremmar:**

Z Li = 410 - 1803 mm
A Li = 382 - 5477 mm
B Li = 570 - 11957 mm
C Li = 858 - 10733 mm
D Li = 2500 - 15184 mm
E Li = 4575 - 15160mm

SP – mantlade smalkilremmar:

SPZ Ld = 587 - 3550 mm
SPA Ld = 657 - 4500 mm
SPB Ld = 1250 - 8000 mm
SPC Ld = 2000 – 12500 mm

XDV® Extra duty mantlade klassiska kilremmar:

XDV38 (SPZ/Z skivor) Le = 381 - 1905mm
XDV48 (SPA/A skivor) Le = 432 - 2972mm
XDV58 (SPB/B skivor) Le = 584 - 2616mm

LINEA-X råkantade tandade smalkilremmar:

XPZ Ld = 512 - 3550 mm
XPA Ld = 667 - 4500 mm
XPB Ld = 1250 - 5000 mm
XPC Ld = 2000 - 5000 mm

ESAFLEX® dubbelsidiga kilremmar:

AA L = 1350 - 3305 mm
BB L = 1345 - 7655 mm
CC L = 2015 - 10725 mm

PLURIPAND® gruppkilremmar:

B Li = 1778 - 5004 mm
C Li = 2489 - 4953 mm
3V Le = 850 - 3550 mm
5V Le = 1270 - 9000 mm
8V Le = 2540 - 15250 mm
3VX Le = 630 - 3550mm
5VX Le = 1270 - 5080mm

Poly-V remmar:

H L = 594 - 1975mm
J L = 350 - 2489 mm
L L = 1270 - 6096 mm